



DIESEL/ELECTRIC DRIVE AUTO PRIME HIGH HEAD PUMP

HH80

Technical Data



Fuel Consumption: 2.4 L/hr @ BEP 1400rpm WMR
 Fuel Capacity: 340 litres

Pumpset Dimensions

Width: 1250 mm Height: 1900 mm
 Length: 2340 mm Dry Weight: 1540 kg

Materials of Construction

Pump Casing: S.G. IRON 400/12
 Suction Cover: S.G. IRON 400/12
 Air Separation Tank: S.G. IRON 400/12
 Bearing Bracket: S.G. IRON 400/12
 Pump Shaft: 431 Stainless Steel
 Impeller: 316 Stainless Steel
 Wearplates: 316 Stainless Steel
 Mechanical Seal: Silicon Carbide/Silicon Carbide
 N.R.V.:(Ball Type): S.G. IRON 400/12

Design Details

Pump Description: Single Stage, volute type, 3 bladed fully open Centrifugal pump
 Suction Flange: 75 mm
 Delivery Flange: 75 mm
 Nominal Casing Thickness: 10 mm
 Solids Handling Size: 25 mm
 Operating Speed: MIN: 1400rpm MAX: 2400rpm
 Maximum Head: 105 m
 Maximum Capacity: 29 L/sec

